



XG932 III
Wheel Loader



Wheel Loader XG932 III



Optional equipment

- Cold start, Three-stage air filter (desert type)
- Rock bucket, Coal bucket, Woodchip bucket, Light material bucket, Long boom
- Log grapple, Grass grapple, Snow remover (mechanism type)
- Third hydraulic function, Redirector EATON, Hydraulic hose PARKER
- Heating system, Cold air-conditioning system, Air-conditioning system (cool & warm)
- Seat Grammer, Luxurious seat Grammer (with Arm rest, Pillow, Seat belt)
- Neutral start protectors, Mobile warning light, Double working light for work condition at night
- ICI painting

Excellent performance

- Torque converter and transmission derive from 4T loader, excellent versatility.
- Patent hydraulic technology, excellent performance and energy-saving and low oil consumption.
- The standard lift arm reach the dump height of 5T loader (3060mm).
- Sufficient structure intensity reserve and low failure rate of the machine tested in domestic market.



Specifications and overall dimensions

Operating weight	10600 kg	Overall length	6950 mm
Rated power	92 kw (Yuchai YC6B125-T10)	Overall width	2400 mm
Bucket capacity	1.8 m ³	Overall height	3150 mm
Rated load	3200 kg	Dump height	3060 mm
Travel speeds		Dumping reach	1008 mm
Forward I	12 km/h	Transmission	XG
Forward II	40 km/h	Speed ranges(F/R)	2/1
Reverse I	16 km/h	Fuel tank capacity	150 L
Turning angle	±35 °	Hydraulic oil tank capacity	140 L
Turning radius	5860 mm	Lifting time	≤6.5 s
Tires	17.5-25-12 PR	Total cycle time	≤10.5 s

Content and specification are subject to change without notice



XIAMEN XGMA MACHINERY CO.,LTD.

XIAMEN XGMA INTERNATIONAL TRADE CO.,LTD.

Add:6th Floor,No.11,East Hexiang Road,Xiamen,361004,China

Tel:0086-592-5822739/5860534 Fax:0086-592-5822378

E-mail:marketing@xiagong.com

http://www.xgma.com.cn/ www.xiagong.com